



Technical Data Sheet

Product Profile

PRODUCT NAME: PPS-7200 Water-Based Surface Cleaner

DESCRIPTION: PPS-7200 is a VOC-compliant cleaner designed to remove contaminants from painted parts, plastic, bare metal, and gelcoat prior to painting. PPS-7200 meets VOC requirements in compliant and national rule areas.

Instructions

- Use PPS-7200 before and after sanding, and prior to painting.
- PPS-7200 can be applied with a sprayer or a clean rag.
- After applying, wipe the area until dry with a clean, lint-free rag.
- Wipe the area with a tack cloth immediately before painting to remove any dust.
- If applying to bare metal, take care to wipe dry quickly. Prolonged contact with bare metals can cause the surface to oxidize.
- PPS-7200 should not be used on body filler or glazing putty. Porous surfaces will trap water, which can cause problems when painted.

Basic Information

GENERAL

Appearance	Clear liquid
Shelf Life	One Year (unopened)
VOC	0.2 lb/gal (24 g/L)

SUBSTRATES:

- Bare metal
- Fiberglass
- Most plastics
- Previously painted surfaces
- Freshly sanded surfaces
- Cured primer, basecoat, and clearcoat
- Recommended substrate temperatures: 50° F - 100° F.